

CONTOUR GENERATION FOR MASK
PROJECTION STEREOLITHOGRAPHY
3D PRINTING

FAEIZ AZIZI BIN ADNAN

Master of Science

UNIVERSITI MALAYSIA PAHANG



SUPERVISOR'S DECLARATION

I hereby declare that I have checked this thesis, and in my opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Master of Science

(Supervisor's Signature)

Full Name : DR. FADHLUR RAHMAN BIN MOHD ROMLAY

Position : SENIOR LECTURER

Date : 12 July 2019



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : FAEIZ AZIZI BIN ADNAN

ID Number : MFM15002

Date : 12 July 2019

CONTOUR GENERATION FOR MASK PROJECTION
STEREOLITHOGRAPHY 3D PRINTING

FAEIZ AZIZI BIN ADNAN

Thesis submitted in fulfilment of the requirements
for the award of the degree of
Master of Science

Faculty of Mechanical & Manufacturing Engineering
UNIVERSITI MALAYSIA PAHANG

JULY 2019

ACKNOWLEDGEMENTS

Here I would to express my deepest gratitude upon the thesis completion. It is all thanks to my supportive parent. They have been supporting me all way from the beginning of this study until the end. Without their support, I would not have managed to complete this thesis. Their encouragement keeps me motivated throughout the study.

I would also like to thank my supervisor Dr. Fadhlur Rahman Bin Mohd Romlay for his guidance during my study. The research field is totally new to me. For someone who has no prior knowledge and skill for research works, I often find myself lost and misdirected. Most of the time, Dr. Fadhlur patiently guided me and taught me how to be a good researcher.

Next, I would like to thank Siti Noor Sheeren Binti Manan for her supports on my study. She always kept pushing me to finish my study. This motivation helps me in pursuing the thesis completion. Her support also encourages me to complete this study.

This research is funded by Universiti Malaysia Pahang (UMP) by the research grant number RDU160387. I would like to thank UMP for the fund. Without it, this research would be difficult to complete. This fund helped in purchasing the components needed for this research. The fund also supported me to overcome my financial issues. Other than that, UMP also provided excellent equipment and facilities to assist the research. I wish that the government will increase their research budget allocations for UMP in the future so that many more high impact researches can be produced. Also, special thanks to Faculty of Manufacturing Engineering UMP for providing the space and equipment for this study.

ABSTRAK

Kemajuan terkini dalam teknologi pencetakan 3D telah membawa kepada penghasilan mesin pencetakan 3D berasaskan pancaran-bertopeng. Proses ini menggunakan tenaga cahaya UV bagi membentuk objek nyata dari resin penyembuhan-foto. Pancaran kontur dijanakan dengan mengiris model CAD STL kepada lapisan-lapisan kontur 2D yang kemudiannya disalurkan kepada alat pemancar lapisan demi lapisan berasaskan ketinggian binaan. Pengkomputan bagi penjanaan lapisan-lapisan kontur 2D adalah sangat intensif. Algoritma penjanaan kontur yang sedia ada memerlukan masa pengkomputan yang lama. Ini kerana algoritma tersebut perlu mengiris dan mengkomput setiap satu lapisan sesebuah model STL sebelum proses pencetakan bermula. Dalam usaha bagi mengurangkan masa pengkomputan, algoritma yang baru dan lebih pantas diperlukan. Lantaran itu, algoritma penjanaan kontur pantas dibentangkan di dalam kajian ini. Kaedah ini menghasilkan satu lapisan kontur secara pantas apabila parameter ketinggian binaan disuapkan ke dalam algoritma tersebut. Algoritma tersebut mengandungi beberapa algoritma seperti algoritma pengirisan, algoritma pemetaan garisan pixel, dan algoritma gelungan kontur. Algoritma pengirisan menggunakan model persilangan garisan-satah untuk menghasilkan segmen garisan rawak apabila ia menerima satu faset STL. Segmen-segmen garisan ini kemudiannya dipetakan berdasarkan resolusi alat pemancar dengan menggunakan algoritma pemetaan garisan pixel. Kemudian, garisan-garisan pixel tersebut dihubungkan untuk membentuk satu atau lebih gelungan kontur melalui algoritma gelungan kontur. Hasil dari setiap algoritma-algoritma tersebut dikaji secara mendalam. Pengukuran masa pengkomputan diambil menggunakan objek <QElapsedTimer> di dalam Qt Creator dan diukur dalam millisaat. Keputusan hasil kajian menyatakan algoritma-algoritma tersebut menjanakan lapisan-lapisan kontur dengan tepat. Malah dengan menggunakan model STL berpoligon tinggi, algoritma penjanaan kontur masih dapat menjanakan lapisan kontur secara purata 960.15% lebih pantas dari algoritma Park dan 169.15% lebih pantas dari perisian komersial Slic3r.

ABSTRACT

Recent advancement in 3D printing technology has led to the development of projection mask stereolithography 3D printing process. This process harnesses the power of UV light contour projection to cure photocurable resin. The contour projection is generated by slicing STL CAD model into layers of 2D contours which is then fed into the UV projection device layer-by-layer with respect to the build height. Generation of the layers are computationally intensive. Existing contour generation algorithm requires long computational time to generate the contour layers especially for high polygon models. This is because the existing approach has to slice and compute every single layer of the STL model before the printing process starts. In an effort to reduce the computational time, a new and faster algorithm is required. Thus, a real-time contour generation algorithm is presented in this research. The real-time contour generation approach instantly generates single layer of contour whenever the build height parameter is fed into the algorithm. The algorithm composes of multiple algorithms such as slicing algorithm, pixel line mapping algorithm, and the contour loop algorithm. The proposed slicing algorithm uses line-plane intersection model to generate arbitrary line segment when it receives an STL facet. These line segments are mapped based on the projection device display resolution by the pixel-line mapping algorithm. Then, the pixelated line segments are connected to form single/multiple contour loops using contour loop algorithm. The results of each algorithms are thoroughly evaluated. Computation time measurement is taken using <QElapsedTimer> object in Qt Creator and measured in milliseconds. It is later found that the algorithms able to correctly generates the contour projection layers. Even with the high polygon STL model, the contour generation algorithm able to perform on average 960.15% faster than Park algorithm and 169.18% faster than commercial software Slic3r.

TABLE OF CONTENT

DECLARATION	
TITLE PAGE	
ACKNOWLEDGEMENTS	ii
ABSTRAK	iii
ABSTRACT	iv
TABLE OF CONTENT	v
LIST OF TABLES	viii
LIST OF FIGURES	ix
LIST OF SYMBOLS	x
LIST OF ABBREVIATIONS	xi
CHAPTER 1 INTRODUCTION	1
1.1 DLP Projection Mask Stereolithography	1
1.2 Contour Generation Algorithm in Projection Mask Stereolithography	3
1.3 Problem Statement	4
1.4 Research Objectives	5
1.5 Research Scope	5
CHAPTER 2 LITERATURE REVIEW	6
2.1 Introduction	6
2.2 Mask Projection Stereolithography	6
2.2.1 Photopolymerization	7
2.2.2 Curing Depth Model of Photopolymerization	7

2.3	STL Format	13
2.3.1	Types of STL	13
2.3.2	Issues of STL	15
2.4	Slicing Algorithm	18
2.4.1	Fundamental of Slicing Algorithm	18
2.4.2	Facet-Plane Intersection Case Handling	20
2.4.3	Data Structure	21
2.4.4	Type of Slicing Algorithm	22
2.5	Contour Loop Algorithm	24
2.6	Summary	26
CHAPTER 3 METHODOLOGY		29
3.1	Introduction	29
3.2	STL Data Management	30
3.3	Slicing Algorithm	30
3.3.1	Case Handler for Facet-Plane Interaction	31
3.3.2	Formulation of Slicing	32
3.3.3	Line to Pixel Mapping	34
3.3.4	Algorithm Structure	37
3.4	Contour Loop Algorithm	38
3.5	Computational Time Measurement	40
3.6	Test Environment	41
CHAPTER 4 RESULTS AND DISCUSSION		42
4.1	Introduction	42
4.2	Sliced Model Output	42

4.3	Slicing Algorithm Performance	45
4.4	Contour Loop Performance	48
4.4.1	Number of Intersecting Facet at Different Slicing Height	52
4.4.2	Contour Loop Counts	55
4.5	Total Computational Time	59
4.6	Visualization of Contour Generation Algorithm	63
4.7	Comparison of Slicing and Contour Loop algorithms	64
CHAPTER 5 CONCLUSION		68
5.1	Conclusion	68
5.2	Future Work	69
REFERENCES		71
APPENDIX A ADDITIONAL SLICING RESULT		76
APPENDIX B PSEUDOCODE (VB.NET)		79
APPENDIX C PSEUDOCODE (C++)		88
APPENDIX D PSEUDOCODE (MATLAB)		98

LIST OF TABLES

Table 1.1	Classification of 3D printer	2
Table 3.1	Definition of interaction cases	31
Table 4.1	Time measurement for slicing algorithm	45
Table 4.2	Time measurement for contour loop algorithm	49
Table 4.3	Number of intersecting facet at each slicing height	52
Table 4.4	Number of loop counts at each slicing height	55
Table 4.5	Calculated normalized correlation of each STL model	59
Table 4.6	Total computational time required for each slicing height	60
Table 4.7	Time measurement and comparison for slicing algorithm	65
Table 4.8	Time measurement and comparison for contour loop algorithm	66
Table 4.9	Time measurement and comparison for total computational time	67

LIST OF FIGURES

Figure 1.1	Staircase effect caused by uniform slicing thickness	4
Figure 2.1	Surface topology of the curing space	9
Figure 2.2	Curing profile of single axis laser scanning	10
Figure 2.3	Domain of single axis laser scanning model	11
Figure 2.4	Hole at a vertex and overlapping facets	16
Figure 2.5	Facet intersecting with slicing plane	19
Figure 2.6	Possible intersection cases	20
Figure 2.7	Circular approximation for layer error and thickness	24
Figure 3.1	Flowchart of Research Methodology	29
Figure 3.2	Possible facet-plane interaction	31
Figure 3.3	Facet-Plane intersection model	32
Figure 4.1	Sliced model (Sphere) with colour mapped total computational time	43
Figure 4.2	Sliced model (Dragon) with colour mapped total computational time	43
Figure 4.3	Sliced model (Tower) with colour mapped total computational time	44
Figure 4.4	Stacked contours Alien model (side slicing)	63
Figure 4.5	Stacked contours Dragon model (bottom-up slicing)	63
Figure 4.6	Stacked contours Liver model (bottom-up slicing)	64
Figure 4.7	Stacked contours Walnut model (bottom-up slicing)	64

LIST OF SYMBOLS

C_d	Cure Depth
D_p	Depth of Penetration
E_{\max}	Maximum Energy of Laser
E_c	Critical Energy Dosage
α	Photochemical Parameter
β	Photonics Parameter
c	Speed of Light
h	Planck's Constant
N_{av}	Avogadro Constant
P_L	Laser Power
W_o	Beam Width
k_t	Termination Constant
k_p	Propagation Constant
p_c	Extent of Polymerization
ϵ	Molar Extinction Coefficient
λ	Wavelength
ϕ	Quantum Yield
PI	Photoinitiator Concentration
z_c	Cure Depth
x	X component
y	Y component
z	Z component
P_o	Starting point of the line segment
P_f	Ending point of the line segment
s	Interpolation parameter
AR	Aspect Ratio
AR'	Modified Aspect Ratio
R, V, W	Piecewise Variable
NC	Normalized Correlation
O	Big-O Notation

LIST OF ABBREVIATIONS

2D	Two-Dimensional
2PP	Two-Photon Polymerization
3D	Three-Dimensional
3DP	Binder Jetting
AM	Additive Manufacturing
ASCII	American Standard Code for Information Interchange
CAD	Computer Aided Design
CAM	Computer Aided Manufacturing
CLIP	Continuous Liquid Interface Printing
CMM	Coordinate Measurement Machine
CNC	Computer Numerical Control
CPU	Central Processing Unit
CSV	Comma-separated Value
CT	Contour Time
DIW	Robocasting
DLP	Digital Light Processing
DMD	Digital Micro-mirror Device
EBM	Electron Beam Melting
ECC	Efficient Contour Construction
FDM	Fused Deposition Modeling
GB	Giga-Byte
IF	Intersecting Facet
LC	Loop Count
LM	Layered Manufacturing
LOM	Laminated Object Manufacturing
PC	Personal Computer
RAM	Random Access Memory
RP	Rapid Prototyping
SD	Standard Deviation
SLA	Stereolithography 3D Printing
SLM	Selective Laser Melting

SLS	Selective Laser Sintering
STL	STereoLithography CAD format
UV	Ultraviolet

REFERENCES

- Barequet, G., & Sharir, M. (1995). Filling gaps in the boundary of a polyhedron. *Computer Aided Geometric Design*, 12(2), 207–229. [https://doi.org/10.1016/0167-8396\(94\)00011-G](https://doi.org/10.1016/0167-8396(94)00011-G)
- Bloomenthal, J. (1988). Polygonization of implicit surfaces. *Computer Aided Geometric Design*, 5(4), 341–355. [https://doi.org/10.1016/0167-8396\(88\)90013-1](https://doi.org/10.1016/0167-8396(88)90013-1)
- Boddapati, A. (2010). *Modeling Cure Depth During Photopolymerization of Multifunctional Acrylates*. Georgia Institute of Technology.
- Cătălin IANCU, P., Daniela IANCU, E., & Alin STĂNCIOIU, D. (2010). From Cad Model to 3D Print Via STL Format. *Academica Brâncuși Târgu Jiu*, 1(1), 1844–640.
- Choi, S. H., & Kwok, K. T. (1999). A Memory Efficient Slicing Algorithm for Large STL Files. In *Proceedings of the 31st International Conference on Computers and Industrial Engineering* (pp. 155–162).
- Dendukuri, D., Panda, P., Haghighoie, R., Kim, J. M., Hatton, T. A., & Doyle, P. S. (2008). Modeling of oxygen-inhibited free radical photopolymerization in a PDMS microfluidic device. *Macromolecules*, 41(22), 8547–8556. <https://doi.org/10.1021/ma801219w>
- Dizon, J. R. C., Espera, A. H., Chen, Q., & Advincula, R. C. (2018). Mechanical characterization of 3D-printed polymers. *Additive Manufacturing*, 20, 44–67. <https://doi.org/10.1016/j.addma.2017.12.002>
- Gao, F., Yang, Y., & Li, L. (1999). Visible light photopolymerization of Methylmethacrylate coninitiated with titanocene and ketocoumarin dye. *Chinese Journal of Polymer Science*, 17(5), 465–470.
- Gregori, R. M. M. H., Volpato, N., Minetto, R., & Silva, M. V. G. Da. (2014). Slicing Triangle Meshes: An Asymptotically Optimal Algorithm. *2014 14th International Conference on Computational Science and Its Applications*, 252–255. <https://doi.org/10.1109/ICCSA.2014.58>
- Hayasi, M. T., & Asiabanpour, B. (2009). Machine path generation using direct slicing from design-by-feature solid model for rapid prototyping. *International Journal of Advanced Manufacturing Technology*, 45(1–2), 170–180. <https://doi.org/10.1007/s00170-009-1944-8>
- Hemant, P., Kulkarni, P., & Thokale, M. (2015). 3D Printing Technology. *International Journal of Multidisciplinary Research and Development*, 2(3), 351–358. Retrieved from <http://3dprintingindustry.com/3d-printing-basics-free-beginners-guide/technology/>
- Huang, S. H., Zhang, L. C., & Han, M. (2002). An effective error-tolerance slicing algorithm

- for STL files. *International Journal of Advanced Manufacturing Technology*, 20(5), 363–367. <https://doi.org/10.1007/s001700200164>
- Huang, X., Yao, Y., & Hu, Q. (2012). Research on the rapid slicing algorithm for NC milling based on STL model. *Communications in Computer and Information Science*, 325 CCIS(PART 3), 263–271. https://doi.org/10.1007/978-3-642-34387-2_30
- Jacob, G. G. K., Kai, C. C., & Mei, T. (1999). Development of a new rapid prototyping interface. *Computers in Industry*, 39(1), 61–70. [https://doi.org/10.1016/S0166-3615\(98\)00124-9](https://doi.org/10.1016/S0166-3615(98)00124-9)
- Jacobs, P. F. (1992). Fundamentals of Stereolithography. *Society of Manufacturing Engineers*, (July), 196–211. <https://doi.org/10.1017/CBO9781107415324.004>
- Jing Hu. (2017). Study On STL-Based Slicing Process For 3D Printing. *Solid Freeform Fabrication*, 885–895.
- Kang, H. W., Park, J. H., & Cho, D. W. (2012). A pixel based solidification model for projection based stereolithography technology. *Sensors and Actuators, A: Physical*, 178, 223–229. <https://doi.org/10.1016/j.sna.2012.01.016>
- Kirschman, C., & Jara-Almonte, C. (1992). A parallel slicing algorithm for solid freeform fabrication processes. *Solid Freeform Fabrication Symposium*.
- Kitano, H. (2012). Advances In light-induced polymerizations : I . Shadow cure in free radical photopolymerizations , II . Experimental and modeling studies of photoinitiator systems for effective polymerizations with LEDs. *PhD Dissertation*, 195.
- Koc, B., Ma, Y., & Lee, Y. S. (2000). Smoothing STL files by Max-Fit biarc curves for rapid prototyping. *Rapid Prototyping Journal*, 6(3), 186–203. <https://doi.org/10.1108/13552540010337065>
- Kodama, H. (1981). Automatic method for fabricating a three-dimensional plastic model with photo-hardening polymer. *Review of Scientific Instruments*, 52(11), 1770–1773. <https://doi.org/10.1063/1.1136492>
- Królikowski, M., & Grzesiak, D. (2014). Technological Restrictions of Lightweight Lattice Structures Manufactured by Selective Laser Melting of Metals. *Advances in Manufacturing Science and Technology*, 38(2). <https://doi.org/10.2478/amst-2014-0012>
- Kulkarni, P., Marsan, A., & Dutta, D. (2000). Review of process planning techniques in layered manufacturing. *Rapid Prototyping Journal*. <https://doi.org/10.1108/13552540010309859>
- Kumar, V., & Dutta, D. (1997). An assessment of data formats for layered manufacturing.

- Advances in Engineering Software*, 28(3), 151–164. [https://doi.org/10.1016/S0965-9978\(96\)00050-6](https://doi.org/10.1016/S0965-9978(96)00050-6)
- Lederle, F., Meyer, F., Brunotte, G.-P., Kaldun, C., & Hübner, E. G. (2016). Improved mechanical properties of 3D-printed parts by fused deposition modeling processed under the exclusion of oxygen. *Progress in Additive Manufacturing*, 1(1–2), 3–7. <https://doi.org/10.1007/s40964-016-0010-y>
- Lee, J. H., Prud'homme, R. K., & Aksay, I. a. (2001). Cure depth in photopolymerization: Experiments and theory. *Journal of Materials Research*, 16(12), 3536–3544. <https://doi.org/10.1557/JMR.2001.0485>
- Leong, K. F., Chua, C. K., & Ng, Y. M. (1996). A study of stereolithography file errors and repair. Part 1. Generic solution. *International Journal of Advanced Manufacturing Technology*, 12(6), 407–414. <https://doi.org/10.1007/BF01186929>
- Manmadhachary, A., Ravi Kumar, Y., & Krishnanand, L. (2016). Improve the accuracy, surface smoothing and material adaption in STL file for RP medical models. *Journal of Manufacturing Processes*, 21, 46–55. <https://doi.org/10.1016/j.jmapro.2015.11.006>
- Minetto, R., Volpato, N., Stolfi, J., Gregori, R. M. M. H., & da Silva, M. V. G. (2017). An optimal algorithm for 3D triangle mesh slicing. *CAD Computer Aided Design*, 92, 1–10. <https://doi.org/10.1016/j.cad.2017.07.001>
- Mu, Q., Wang, L., Dunn, C. K., Kuang, X., Duan, F., Zhang, Z., ... Wang, T. (2017). Digital light processing 3D printing of conductive complex structures. *Additive Manufacturing*, 18, 74–83. <https://doi.org/10.1016/j.addma.2017.08.011>
- Pan, X., Chen, K., & Chen, D. (2014). Development of rapid prototyping slicing software based on STL model. *Proceedings of the 2014 IEEE 18th International Conference on Computer Supported Cooperative Work in Design, CSCWD 2014*, (51175395), 191–195. <https://doi.org/10.1109/CSCWD.2014.6846840>
- Pan, Y., Zhou, C., & Chen, Y. (2012). A Fast Mask Projection Stereolithography Process for Fabricating Digital Models in Minutes. *Journal of Manufacturing Science and Engineering*, 134(5), 051011. <https://doi.org/10.1115/1.4007465>
- Pandey, P. M., Reddy, N. V., & Dhande, S. G. (2003). Real time adaptive slicing for fused deposition modelling. *International Journal of Machine Tools and Manufacture*, 43(1), 61–71. [https://doi.org/10.1016/S0890-6955\(02\)00164-5](https://doi.org/10.1016/S0890-6955(02)00164-5)
- Pandey, R. (2014). *Photopolymers in 3D printing applications*.
- Park, S. C. (2003). Tool-path generation for Z-constant contour machining. *CAD Computer Aided Design*, 35(1), 27–36. [https://doi.org/10.1016/S0010-4485\(01\)00173-7](https://doi.org/10.1016/S0010-4485(01)00173-7)

- Piegl, L. A., & Richard, A. M. (1995). Tessellating trimmed nurbs surfaces. *Computer-Aided Design*, 27(1), 16–26. [https://doi.org/10.1016/0010-4485\(95\)90749-6](https://doi.org/10.1016/0010-4485(95)90749-6)
- Ranellucci, A., & Lenox, J. (2011). Slic3r - G-code generator for 3D printers. Retrieved from <http://www.slic3r.org/>
- Szilvsi-Nagy, M., & Mátyási, G. (2003). Analysis of STL files. *Mathematical and Computer Modelling*, 38(7–9), 945–960. [https://doi.org/10.1016/S0895-7177\(03\)90079-3](https://doi.org/10.1016/S0895-7177(03)90079-3)
- Tang, Y. (2005). *Stereolithography Cure Process Modeling*. Georgia Institute of Technology.
- Tang, Y., Henderson, C. L., Muzzy, J., & Rosen, D. W. (2004). Stereolithography Cure Process Modeling Using Acrylate Resin. *Fifteenth Solid Freeform Fabrication (SFF) Symposium*, 612–623. <https://doi.org/10.1017/CBO9781107415324.004>
- Tian, R., Liu, S., & Zhang, Y. (2018). Research on fast grouping slice algorithm for STL model in rapid prototyping. *Journal of Physics: Conference Series*, 1074, 012165. <https://doi.org/10.1088/1742-6596/1074/1/012165>
- Topçu, O., Taşcıoğlu, Y., & Ünver, H. Ö. (2011). A Method for Slicing CAD Models in Binary STL Format. *6th International Advanced Technologies Symposium (IATS'11)*, (May), 141–148. Retrieved from <http://web.firat.edu.tr/iats/cd/subjects/Manufacturing/MTE-31.pdf>
- Tumbleston, J. R., Shirvanyants, D., Ermoshkin, N., Januszewicz, R., Johnson, A. R., Kelly, D., ... Desimone, J. M. (2015). Continuous liquid interface production of 3D objects. *Science*, 347(6228), 1349–1352.
- Tyvaert, I., Fadel, G., & Rouhaud, E. (1999). A methodology to create STL files from data point clouds generated with a coordinate measuring machine. *Annual International Solid Freeform Fabrication Symposium*, 47–58.
- Vatani, M., Rahimi, A. R., Brazandeh, F., & Sanati Nezhad, A. (2009). An enhanced slicing algorithm using nearest distance analysis for layer manufacturing. *Proceedings of World Academy of Science, Engineering and Technology*, 37(1), 721–726. Retrieved from <http://www.waset.ac.nz/journals/waset/v49/v49-130.pdf>
- Wang, D. X., Guo, D. M., Jia, Z. Y., & Leng, H. W. (2006). Slicing of CAD models in color STL format. *Computers in Industry*, 57(1), 3–10. <https://doi.org/10.1016/j.compind.2005.03.007>
- Wong, H.-T. T., Huang, Y., Tsang, S.-C., & Lam, M.-L. (2017). Real-time model slicing in arbitrary direction using octree. *ACM SIGGRAPH 2017 Posters on - SIGGRAPH '17*, 1–2. <https://doi.org/10.1145/3102163.3102185>

- Wong, K. V., & Hernandez, A. (2012). A Review of Additive Manufacturing. *ISRN Mechanical Engineering*, 2012, 1–10. <https://doi.org/10.5402/2012/208760>
- Wu, T., & Cheung, E. H. M. (2006). Enhanced STL. *International Journal of Advanced Manufacturing Technology*, 29(11–12), 1143–1150. <https://doi.org/10.1007/s00170-005-0001-5>
- Xu, H., Weihua, J., Li, M., & Li, W. (2017). A slicing model algorithm based on STL model for additive manufacturing processes. *Proceedings of 2016 IEEE Advanced Information Management, Communicates, Electronic and Automation Control Conference, IMCEC 2016*, 1607–1610. <https://doi.org/10.1109/IMCEC.2016.7867489>
- Ye, H., Zhou, C., & Xu, W. (2017). Image-Based Slicing and Tool Path Planning for Hybrid Stereolithography Additive Manufacturing. *Journal of Manufacturing Science and Engineering*, 139(7), 071006. <https://doi.org/10.1115/1.4035795>
- Zhang, Z., & Joshi, S. (2015). An improved slicing algorithm with efficient contour construction using STL files. *International Journal of Advanced Manufacturing Technology*, 80(5–8), 1347–1362. <https://doi.org/10.1007/s00170-015-7071-9>
- Zheng, X., Cheng, K., Zhou, X., Lin, J., & Jing, X. (2018). An adaptive direct slicing method based on tilted voxel of two-photon polymerization. *International Journal of Advanced Manufacturing Technology*, 96(1–4), 521–530. <https://doi.org/10.1007/s00170-017-1507-3>
- Zhou, M. Y., Xi, J. T., & Yan, J. Q. (2004). Adaptive direct slicing with non-uniform cusp heights for rapid prototyping. *International Journal of Advanced Manufacturing Technology*, 23(1–2), 20–27. <https://doi.org/10.1007/s00170-002-1523-8>